

INDOOR DIGITAL SIGNAGE

LARGE SIZE FORMAT APPLIED SCREEN

CLASS

MODEL

65"

D65AMNI

KEY FEATURES

- LED BLU, Slim Design
- Power Consumption Reduced at 40% Compared to Normal Display
- Built in Video Wall Function
- High Connectivity
- Remote Control (RS232)
- Support HDMI 2.0 & VGA (1080p)
- USB Plug & Play (JPG & MP4)
- High Fidelity Audio Output (SPDIF)
- Touch Screen



HYUNDAI

Broadcast your branding with Hyundai Digital Signage!

Thanks to the advanced product design, Hyundai Digital Signage Display meets requirements for various digital signage solutions. Not only take advantage from slim and simple design, but also think more about our future environment, saving energy up to 40 percent. LED technologies bring more than just expected.



HYUNDAI

SPECIFICATIONS

Model	D65AMNI
Screen Size (diagonal)	65"
Active Display Area (inch / mm)	56.24 x 31.64 1428.5 x 803.6
Resolution	1920 x 1080
Aspect Ratio	16 : 9
Display Colors	1.06B
Brightness (cd/m ² ; typ.)	450
Contrast Ratio	1300 : 1
Response Time (ms; GTG)	10
Viewing Angle	178°/178°
Lifetime (hours)	50,000
Backlight type	LED
Available Touch Point	1 ~ 10
Response Time (ms)	1P Touch : 8 / 10P Touch : 13
Tempered Glass	Transmission: 90%, Thickness: 5mm
Available object size for Touch (mm)	Touch : Ø 7 Stylus : Ø 8
Interface	USB 1.0 / USB 2.0 Full speed
Detection Method	Infrared Rays
HID (Mouse Click)	Windows / Linux / Mac / Android
Resolution	1920 x 1080
Input	1xVGA 3xHDMI 1xPC Audio 1xRS232C 1xUSB(MMP) 1xIR 1xDPI(Optional) 1xRJ45(Optional)
Media Player (USB)	Movie : MPEG-2 MPEG-4 Photo : JPEG PNG BMP Music : MP3
Output	1xHDMI 1xIR 1xRS232C 1xSPDIF Audio-Line Out Speaker(Optional)
Power	Input Voltage : 100 ~ 240V AC Power consumption : 120 W
Features	Auto Power Control : Yes Auto Brightness Sensor : No
Operation	Temperature (°C) : 0 - 40 Humidity (%) : 20 - 80 OSD Language : 12 Lang
Dimension	Set Size : W x H x D (inch mm) : 58.08 x 33.39 x 3.04 1475.2 x 848.2 x 77.2 Bezel Size : U/D/L/R (inch mm) : 0.79 / 0.79 / 0.79 / 0.79 20.05 / 20.05 / 20.05 / 20.05 Wall Mounting hole : WxH (mm) : 400 x 400 / 600 x 400 (M6)
Weight	Set (lb kg) : T.B.D

Specifications and design are subject to change without notice. See our website for detailed information.

HEAD OFFICE - HYUNDAI IT CO., LTD.
5F, 36, Sangil-ro 10-gil, Gangdong-gu, Seoul, 05288 Korea
Tel. +82 70 7008 0151 E-mail: ssoh@hdit.co.kr
www.hdit.co.kr

HYUNDAI IT AMERICA CORP.
2051 Junction AVE., Suite 112 San Jose, CA 95131, USA
Tel. +1 408 954 8920 email : sales@hyundaita.com
www.hyundait.com

HYUNDAI IT EUROPE GMBH
Borsig Str. 11-13
65205 Wiesbaden, Germany
Tel. +49(0) 6122-70342-10 email : info@hyundait.eu
www.hyundait.eu

LARGE SIZE FORMAT APPLIED SCREEN

MODEL

CLASS

D65AMNI

65"

FEATURES

LED Backlight

HYUNDAI's public displays with LED backlight bring the advantage of up to 40% lower power consumption, compared to displays with CCFL backlight.

Easy operating OSD menu, Remote control

In order to setup a multi display wall, the single units are linked by a daisy chain connection over DVI interface. The configuration of each display can be easily set-up over the on-screen menu or the RS232C interface.


Cost Effective Media Player

HYUNDAI IT's display serves in-built media player enables to play various range of content including video, images and photos. Thanks to this solution, no need for an additional media player for cost and space efficiency.

Multi Touch Screen Function

As an option, all HYUNDAI Digital Signage Displays can be equipped with touch screen functionality. Based on the infrared ray matrix technology, Digital Signage display can operate with either single- or multi-touch mode. This makes the HYUNDAI's Digital Signage display more advanced touch screen solution for the interactive display.

DIMENSIONS



UPDATE : JUL. 2017