

## مشخصات فنی چاپگرهای سه بعدی کمپانی بیلدر هلند

Industrial			Premium			Desktop		Models Items	
Extreme 2000	Extreme 1500	Extreme 1000	Larg	Medium	Small	Big Doul Feed	Doul Feed		
1000×1000×2000 mm(L×W×H)	1500×600×1600 mm(L×W×H)	1016×1006×1500 mm(L×W×H)	370×380×890 mm (L×W×H)	370×380×710 mm (L×W×H)	370×380×495 mm (L×W×H)	385×370×900 mm (L×W×H)	385×370×400m m (L×W×H)	Printer Dimensions	General Specifications
• Aluminium	• Aluminium	• Aluminium	• Steel • Powder coated	• Steel • Powder coated	• Steel • Powder coated	• Steel • Powder coated	• Steel • Powder coated	Frame	
250kg	225kg	220kg	24kg	22kg	18kg	25kg	20 kg	Weight	
USB,Stand-Alone,SD Crad	USB,Stand-Alone,SD Crad	USB,Stand-Alone,SD Crad	USB,WiFi	USB,WiFi	USB,WiFi	USB,Stand-Alone,SD Crad	USB,Stand-Alone,SD Crad	Connections	
---	---	---	4.3 inch	4.3 inch	4.3 inch	---	---	Full Color Touch Screen	
---	---	---	480×272 Pixels	480×272 Pixels	480×272 Pixels	---	---	Camera	
700×700×1820 mm(L×W×H)	1100×500×820 mm(L×W×H)	700×700×820 mm(L×W×H)	205×215×600 mm(L×W×H)	205×215×400 mm(L×W×H)	205×215×200 mm(L×W×H)	220×210×664 mm(L×W×H)	220×210×164m m(L×W×H)	Build Size	3D Prints
0.05-0.6mm Depending on nozzle size	0,05 – 0,6 mm Depending on nozzle size	0.05-0.6mm Depending on nozzle size	0.02-0.3mm	0.05-0.3mm	0.05-0.3mm	0.05-0.3mm	0.05-0.3mm	Layer height Resolution	
0.4/0.8/1.2 mm	0.4/0.8/1.2 mm	0.4/0.8/1.2 mm	0.4mm	0.4mm	0.4mm	0.4mm	0.4mm	Nozzle Diameter	
Heated bed 20-60 degrees	Heated bed 20-60 degrees	Heated bed 20-60 degrees	Heated bed 20-60 degrees	Heated bed 20-60 degrees	Heated bed 20-60 degrees	Removeable glass plate (optional heated bed)	Removeable glass plate (optional heated bed)	Print bed	
PLA-PVA-PET Woodfill-Bronzfill-Flex								Materials	
Repetier, Cura, Kisslicer, Simplify3D								Software	
STL, OBJ, AMF, DAE								File Types	

با تشکر و احترام  
 شرکت مهندسی نقش آور دنا